

Product Name:	ABT-HC-49-TS
Description:	<p>TempLog Premier Glass Door Laboratory Refrigerator 49 Cu. Ft. capacity Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated) Microprocessor temperature controller Adjustable operating temperature range: 1°C - 10°C Touch Screen Digital Temperature Display and Alarm Module Password-protected control panel Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit Active temperature scale bar display Resettable 1-point min/max history Digital 24-hour temperature chart Temperature data logging USB port for data transfer and software updates Real-time operational display clock 4-20mA output Electronic troubleshooting guide Electronic QR Code to access Owner's Manual & technical support contact Information Adjustable alarm volume Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Door ajar alarm Low battery alarm Operation indicator Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts Eight adjustable shelves (adjustable in ½" increments) Keyed door lock Magnetic door gasket for positive seal Heavy duty door handles LED interior lights are safety shielded and switch controlled Swivel casters (adds 4" to height) Probe access port (3/8") White laminated vinyl exterior White aluminum liner and stainless steel floor interior HFC-free refrigerant (R290a), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 54 1/8"W x 31 3/8"D x 82 5/8" H with casters; 78 5/8" H without casters Cycle defrost 115V, 60 Hz, 8.5 Amps, 1/2 HP UL/C-UL listed Shipping weight: 470 lbs.</p>