

Product Name:	ABT-HC-49C-TS
Description:	<p>TempLog Premier Glass Door Chromatography Refrigerator</p> <p>49 Cu. Ft. capacity</p> <p>Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated)</p> <p>Microprocessor temperature controller:</p> <p>Adjustable operating temperature range: 1°C – 10°C</p> <p>Touch Screen Digital Temperature Display and Alarm Module</p> <p>Password-protected Control Panel</p> <p>Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit</p> <p>Active Temperature Scale Bar Display</p> <p>Resettable 1-point Min/Max History</p> <p>Digital 24-hour Temperature Chart</p> <p>Temperature Data Logging</p> <p>USB Port for Data Transfer and Software Updates</p> <p>Real-time Operational Display Clock</p> <p>4-20mA Output</p> <p>Electronic Troubleshooting Guide</p> <p>Electronic QR Code to Access Owner's Manual & Technical Support Contact Information</p> <p>Adjustable Alarm Volume</p> <p>Audible and Visual High/Low Temperature Alarms</p> <p>Sensor Error Alarm</p> <p>Power Failure Alarm</p> <p>Door Ajar Alarm</p> <p>Low Battery Alarm</p> <p>Operation Indicator</p> <p>Alarm Validation (audible, visual, and remote alarm)</p> <p>Alarm Mute with Ring Back</p> <p>Remote Alarm Contacts</p> <p>Eight adjustable shelves (adjustable in ½" increments)</p> <p>Keyed door lock</p> <p>Magnetic door gasket for positive seal</p> <p>Heavy duty door handles</p> <p>LED interior lights are safety shielded and switch controlled</p> <p>Swivel casters (adds 4" to height)</p> <p>One GFCI protected duplex electrical outlet</p> <p>Two 2" access ports with spring loaded self-closing, gasketed metal covers</p> <p>Probe access port (3/8")</p> <p>White laminated vinyl exterior</p> <p>White aluminum liner and stainless steel floor interior</p> <p>HFC-free refrigerant (R290a), foam insulation and packaging</p> <p>Three year parts and labor warranty, plus an additional two year compressor parts warranty</p> <p>Quality certified with 100% unit temperature testing</p> <p>Exterior dimensions: 55 1/8" W x 32 1/16" D x 82 5/8" H with casters; 78 5/8" H without casters</p> <p>Cycle defrost</p> <p>115V, 60 Hz, 8.5 Amps, 1/2 HP</p> <p>UL/C-UL listed</p> <p>Shipping weight: 470 lbs.</p>