	ABT-HC-72C-TS				
D. L. (A)	AD1-110-720-13				
Product Name:					
Description:	TempLog Premier Glass Door Chromatography Refrigerator 72 Cu. Ft. capacity Three swing glass doors, self-closing (energy efficient, double pane vacuum				
	insulated) Microprocessor temperature controller:				
	Adjustable operating temperature range: 1°C – 10°C				
	Touch Screen Digital Temperature Display and Alarm Module				
	Password-protected Control Panel				
	Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit				
	Active Temperature Scale Bar Display				
	Resettable 1-point Min/Max History				
	Digital 24-hour Temperature Chart				
	Temperature Data Logging				
	USB Port for Data Transfer and Software Updates Real-time Operational Display Clock				
	4-20mA Output				
	Electronic Troubleshooting Guide				
	Electronic QR Code to Access Owner's Manual & Technical Support Contact				
	Information				
	Adjustable Alarm Volume				
	Audible and Visual High/Low Temperature Alarms				
	Sensor Error Alarm Power Failure Alarm				
	Door Ajar Alarm				
	Low Battery Alarm				
	Operation Indicator				
	Alarm Validation (audible, visual, and remote alarm)				
	Alarm Mute with Ring Back				
	Remote Alarm Contacts				
	Twelve adjustable shelves (adjustable in ½" increments) Forced draft air circulation				
	Keyed door lock				
	Magnetic door gasket for positive seal				
	Heavy duty door handles				
	LED interior lights are safety shielded and switch controlled				
	Swivel casters (adds 4" to height) One GFCI protected duplex electrical outlet				
	Two 2" access ports with spring loaded self-closing, gasketed metal covers				
	Probe access port (3/8")				
	White laminated vinyl exterior				
	White aluminum liner and stainless steel floor interior				
	HFC-free refrigerant (R290), foam insulation and packaging				
	Three year parts and labor warranty, plus an additional two year compressor parts warranty				
	Exterior dimensions: 79 3/4" W* x 31 3/4" D x 82 5/8" H with casters; 78 5/8" H without				
	casters. *Width w/access ports closed; 87 ¾" width w/access ports open Cycle defrost				
	115V, 60 Hz, 8.5 Amps, 1/2 HP, BTU/HR 7315				
	UL/C-UL listed				
	Shipping weight: 690 lbs.				
	Note: This unit requires two (2) outlets				