



Indigo™ Series 450 Ice Cube Machine

Model: ID-0452A

J1Y-0454A

☐ IY-0455W





Ice Machine Electric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available)

Minimum circuit ampacity:

Air-cooled: 13.2 Water-cooled: Maximum fuse size: 20 amps 1ph

Specifications

BTU Per Hour:

5,400 (average) 6,300 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- Ambient Temperature Range: 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- Space-Saving Design Up to 450 lbs. (204 kgs.) daily ice production and only 30" (76.20 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- **DuraTech™ Exterior** provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available LuminIce™ Growth Inhibitor controls the growth of bacteria and yeast within the foodzone.



Ice Shape



Half Dice (.95 x 2.86 x 2.22 cm)



Dice ½" x ½" x ½" (2.22 x 2.22 x 2.22 cm)













COMPANY WITH QUALITY SYSTEM **CERTIFIED BY DNV** = ISO 9001:2008 =

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







i-450 on B-400 24.50" (62.23 cm) Storage Bin Installation Note Minimum installation A Top/sides: 8" (20.32 cm); Back is 5" (12.7 cm) 32.00" (81.30 cm) 34.00" (86.30 cm) 30.00" (76.20 cm) (A) Electrical Entrance (2) Options 1/2" (1.27 cm) Auxillary Base Drain Socket B 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet (water-cooled units) © 1/2" (1.27 cm) F.P.T. Water Condenser Outlet F 1/2" (1.27 cm) F.P.T. Ice Making Water Drain (G) 3/4" (1.91 cm) Bin Drain

Space-Saving Designs





	i-450 B-400	i-450 B-570		
Height	59.50" 151.13 cm	71.50" 181.61 cn		
Width	30.00" 76.20 cm	30.00" 76.20 cm		
Depth	34.00" 86.30 cm	34.00" 86.30 cm		
Bin Storage	290 lbs. 131.7 kgs.	430 lbs. 195.2 kgs.		

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

Specifications

		Ice	Ice Production 24 Hours		Power Usage kWh/100 lbs. @90°Air/70°F	Water Usage/ 100 lbs. 45.4 kgs. of Ice	ENERGY	
	Model	Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	Potable Water	STAR*	
D		dice	420 lbs.	316 lbs	6.36	20 Gal.	*	
30CE	ID-0452A		191 kgs.	143 kg		75.7 L		
AIR-COOLED	IY-0454A half-dic	half-dice	450 lbs.	335 lbs	5.97	20 Gal.	*	
			204 kgs.	152 kg		75.7 L		
	ID-0453W dice	dice	430 lbs.	360 lbs	4.70	20 Gal.	NA	
) TED	ID-0455W		195 kgs.	163 kg		75.7 L		
WATER-COOLED	IY-0455W half-dice	450 lbs.	360 lbs	4.70	20 Gal.	NA		
			204 kgs.	163 kg	4.70	75.7 L	IVA	
M	* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 169 gal/640 L. * Water-cooled models are excluded from ENERGY STAR qualification.							

Order ice storage bin separately.

Accessories

LuminIce™ **Growth Inhibitor** reduces yeast and bacteria growth for a

cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



Arctic Pure® Water Filters Reduces sediment and chlorine odors for

better tasting ice.



iAuCS® schedules and performs routine ice machine cleaning automatically.



2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com



47688 © 2014 Manitowoc 2/14 Continuing product improvement may necessitate change of specifications without notice