

FFAR25L7



20.75" x 17" x 19.13" (H x W x D)

Commercially approved compact all-refrigerator in white with digital thermostat

Highlights:

Compact size is ideal for use on top of counters

Factory-installed lock provides security you can count on

Digital thermostat for easier and more precise temperature management

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments	
Automatic defrost	No-frost convenience for reduced user maintenance	
Digital thermostat	Electronic controls offer more precision in temperature management, with a readout viewable in Celsius or Fahrenheit	
Factory-installed lock	Keyed lock for a secure interior Rearrange the refrigerator space to fit any sized item or remove shelves for simple cleanup	
Adjustable chrome shelves		
LED lighting	Interior LED lighting offers an energy efficient view in an attractive blue hue	
Reversible door	User-reversible door swing for added flexibility	
Flat door liner	No door shelving allows the unit to accommodate deeper items	
Sealed back	Space-saving design with no exposed coils in the rear offers easy cleanability	





FFAR25L7 Specifications:

Weight	20.25" (51 cm) 20.75" (53 cm) 17.0" (43 cm) 17.75" (45 cm) 19.13" (49 cm) 34.25" (87 cm) 1.7 cu.ft. (48 L) Automatic White ETL ETL-C ETL-S 1.3 115 V AC/60 Hz		
WidthWidth with Door OpenDepthDepth with door at 90°CapacityDefrost TypeDoorCabinetUS Electrical SafetyCanadian Electrical SafetySanitationAmpsVoltage/FrequencyWeightShipping Weight	17.0" (43 cm) 17.75" (45 cm) 19.13" (49 cm) 34.25" (87 cm) 1.7 cu.ft. (48 L) Automatic White ETL ETL-C ETL-C ETL-S 1.3		
Width with Door OpenDepthDepth with door at 90°CapacityDefrost TypeDoorCabinetUS Electrical SafetyCanadian Electrical SafetySanitationAmpsVoltage/FrequencyWeightShipping Weight	17.75" (45 cm) 19.13" (49 cm) 34.25" (87 cm) 1.7 cu.ft. (48 L) Automatic White ETL ETL-C ETL-C ETL-S 1.3		
DepthDepth with door at 90°CapacityDefrost TypeDoorCabinetUS Electrical SafetyCanadian Electrical SafetySanitationAmpsVoltage/FrequencyWeightShipping Weight	19.13" (49 cm) 34.25" (87 cm) 1.7 cu.ft. (48 L) Automatic White ETL ETL-C ETL-C ETL-S 1.3		
Depth with door at 90° Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	34.25" (87 cm) 1.7 cu.ft. (48 L) Automatic White ETL ETL-C ETL-S 1.3		
Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	1.7 cu.ft. (48 L) Automatic White White ETL ETL-C ETL-S 1.3		
Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	Automatic White ETL ETL-C ETL-S 1.3		
Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	White White ETL ETL-C ETL-S 1.3		
Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	White ETL ETL-C ETL-S 1.3		
US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	ETL-C ETL-S 1.3		
Canadian Electrical Safety Sanitation Amps Voltage/Frequency Weight Shipping Weight	ETL-C ETL-S 1.3		
Sanitation Amps Voltage/Frequency Weight Shipping Weight	ETL-S 1.3		
Amps Voltage/Frequency Weight Shipping Weight	1.3		
Voltage/Frequency Weight Shipping Weight			
Weight Shipping Weight	115 V AC/60 Hz		
Shipping Weight			
	55.0 lbs. (25 kg)		
Parts & Labor Warrantv	58.0 lbs. (26 kg)		
	1 Year		
Compressor Warranty	5 Years		
UPC	761101049724		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Chrome		
Shelf Qty	2		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Refrigerant Type	R600a		
Refrigerant Amount	0.6oz.		
High Side PSI	270.0		
Low Side PSI	103.0		
Interior Light	Yes		
Temperature Range	34°F to 43°F		
Dimensions			
Interior Height	16.5" (42 cm)		
Interior Width	13.75" (35 cm)		
Interior Depth	15.0" (38 cm)		
Compressor Step Height			

Compressor Step Width 13	3.75" (35 cm)
Compressor Step Depth	6.0" (15 cm)



