

SBC54OSBIADANK



32.25" x 23.75" x 24.75" (H x W x D)

Built-in undercounter ADA height commercially listed kegerator in stainless steel for outdoor use, tap kit not included

Highlights:

Weatherproof design holds up in the outdoors 32 inch height fits under lower ADA compliant counters Commercially listed to NSF-7 standards

Product Features:

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Tap kit not included	Install your own tapping equipment to create a customized beer cooler	
Designed for 1/6 kegs	Interior can store up to two sixtel kegs	
304 grade stainless steel exterior	Complete stainless steel construction for easy durability in the outdoors	
Factory installed lock	Front lock located towards the top of the door for convenient access, with 2 keys included	
Professional handle	Curved towel bar style handle in brushed stainless steel	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	





SBC54OSBIADANK Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.75" (60 cm)
Depth	24.75" (63 cm)
Depth with Handle	27.25" (69 cm)
Depth with door at 90°	47.0" (119 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatio
Door	Stainless Stee
Cabinet	Stainless Stee
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Shipping Weight	120.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101069593
Kegerator	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Dia
Interior Light	Yes
Fan Type	Exterio
Refrigerant	R600a
Refrigerant Amount	0.64 oz
High Side PSI	180.0
Low Side PSI	80.0
Inter Height	26.25" (67 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF

