

SBC58BLBIADANCFTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap nitro coffee dispenser with stainless steel wrapped door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade dual style tap kit includes everything you need to serve creamy nitro-infused coffee on draft

Commercially listed to NSF-7 standards

Product Features:

| Dispenses nitro-infused coffee | Stout style tap allows you to serve smooth nitro-infused cold brew on tap | |
|--------------------------------|---|--|
| ADA compliant height | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters | |
| Built-in capable | Front-breathing design allows fully recessed installation under counters | |
| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings | |
| Complete tap kit | Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs | |
| Dual tap system | Twin style draft tower allows you to serve from two cornelius style kegs | |
| Stainless steel wrapped door | 304 grade stainless steel for a professional look with lasting durability | |
| Professional handle | Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally | |
| Adjustable thermostat | Interior dial thermostat ensures easy temperature management | |





SBC58BLBIADANCFTWIN Specifications:

| Overview | |
|---|---|
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.25" (82 cm) |
| Width | 23.63" (60 cm) |
| Depth | 22.75" (58 cm) |
| Depth with Handle | 24.25" (62 cm) |
| Depth with door at 90° | 45.0" (114 cm) |
| Capacity | 5.5 cu.ft. (156 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.2 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 110.0 lbs. (50 kg) |
| Shipping Weight | 120.0 lbs. (54 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101069708 |
| Kegerator | |
| Door Swing | RHD |
| 3 | KIID |
| Reversible | Yes |
| | |
| Reversible | Yes |
| Reversible Tap Kit | Yes Yes |
| Reversible Tap Kit Number of Taps | Yes Yes 2 |
| Reversible Tap Kit Number of Taps Thermostat Type | Yes Yes 2 Dial |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light | Yes Yes 2 Dial Yes |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type | Yes Yes 2 Dial Yes Exterior |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant | Yes Yes 2 Dial Yes Exterior R600a |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount | Yes Yes 2 Dial Yes Exterior R600a 0.64 oz. |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI | Yes Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0 |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI | Yes Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0 |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height | Yes Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm) |
| Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height Interior Width | Yes Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm) 21.0" (53 cm) |

| Compressor Step Depth | 5.5" (14 cm) |
|-----------------------|--------------|
| Temperature Range | 34° to 43°F |

