

VT85



33" x 45.75" x 24" (H x W x D)

Laboratory chest freezer capable of -30° C (-22° F) operation; replaces FCL88

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Precise temperature control with a digital thermostat

Factory installed lock provides security you can count on

Product Features:

Commercially approved	UL-S listed to NSF-7 commercial standards and meets UL commercial standard 471
-30° C (-22° F) capable	Low temperature operation ideal for vaccines, pharmaceuticals, and long-term preservation of frozen food
Digital thermostat	Electronic controls for precise temperature management
Thermometer	Provides external temperature readout and includes programmable alarm to warn of temperature variations
Factory installed lock	Keep contents secure with a lock on the lid
Corner protectors	Exterior protection important in high traffic settings
Manual defrost	Temperatures remain stable with an energy efficient manual defrost system
100% CFC free	Environmentally friendly design does not contain ozone-damaging chemicals
CARB Compliant	Environmentally friendly hydrocarbon-based refrigerant for a greener footprint that meets current CARB regulations

VT85 Specifications:

Overview	
Height of Cabinet	33.0" (84 cm)
Width	45.75" (116 cm)
Depth	24.0" (61 cm)
Depth with Handle	25.13" (64 cm)
Capacity	9.0 cu.ft. (255 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101009230
Freezer	
Door Swing	Lift-Up
Thermostat Type	Digital
Refrigerant Type	R600a
Refrigerant Amount	1.94 oz.
Wheels	2

