

ESSEV SERIES

RANGE HOODS

ENERGY STAR® Power Unit Insert

Dimensions

Overall bottom projection - 11"

Height -11"

 $Widths:~28"~\mbox{(for 30" canopy)}~\mbox{and 31.25"}~\mbox{(for 36" canopy or larger)}$

Body

Galvanized steel body with stainless steel fascia. Install at least 24" above the cooking surface.

Lighting

Electronic Quick Start Ballast – Use 2 - Triple 4 pin PL lamps. Maximum 18 Watts each.

Ducting

Vertical ducting: 6" round ducting with all metal outlet adapter and back draft damper

Filters

Dishwasher safe, aluminum mesh grease filters (included).


Blower


3 speed, permanently split capacitor motor. Rated 120 volts,60 hz. with a dual inlet, electronically balanced polymetric centrifugal blower wheel

PERFORMANCE: High - 300 CFM @ 4.5 Sones, HVI Certified

Medium - 200 CFM @ 2.0 Sones, HVI Certified

Low (Normal Operating Speed) - 140 CFM @ 0.7 Sones, HVI Certified





MODEL	CFM HIGH/MED/LOW	SONES HIGH/MED/LOW	LIGHTING	DUCT SIZE	WIDTH	HEIGHT	DEPTH
ESSEV28	300/200/140	4.5/2.0/0.7	2-18W Fluorescent	6" round	28"	11"	11"
ESSEV30	300/200/140	4.5/2.0/0.7	2-18W Fluorescent	6" round	31.25"	11"	11"

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN MO NUMBER NUI	ODEL MBER	СҒМ	IN W.C.	RPM	WATTS	AMPS	SONES QTY		OPTIONAL EQUIPMENT & REMARKS	







U.S.: West Chester, PA 19380 Phone: (877) 304-3785

Fax: (610) 696-8048

Email: sales@airkinglimited.com

Canada: Brampton, Ontario L6T 2J3

Phone: (905) 456-2033 Fax: (905) 456-1015

Email: casales@airkinglimited.com