



MODEL NUMBER:

- **AC POWERED; single inlet**
 - **6058.105** with cast spout, 0.5 GPM pressure compensating, vandal-resistant spray. Includes AC power supply (M950169-0070A).
 - **6058.102** with cast spout, 1.5 GPM pressure compensating, vandal-resistant aerator. Includes AC power supply (M950169-0070A).
- **OPTIONAL 4" or 8" Deck plates**
 - **605P.400** 4" brass deck plate with 1/4" fixation studs and quick spin nuts. (6-1/8"x 2-1/8"x 1/2")
 - **605P.800** 8" brass deck plate with 1/4" fixation studs and quick spin nuts. (10-1/8"x 2-3/8"x 1/2")

GENERAL DESCRIPTION:

Electronic faucet with proximity operation. Colored LED's signal temperature change mode. Vandal-resistant solid brass construction single post mounting. Operates on AC permanent power. Water pressure range from 20 to 125 psi. Dual inlets, built-in checks, and flexible stainless steel 20" reach inlet hoses for connection.

PRODUCT FEATURES:

Vandal-Resistant Brass Body: Durable - Excellent in high use applications.

Power Options:

- **Plug-In** - low voltage transformer (115 VAC supply) with 6 foot long power supply.

Temperature Mixing:

The water temperature gradually decreases/increases to a desired setting through a cyclic mixing valve. After usage, the faucet reverts back to a pre-setting temperature.

Easy and Flexible Installation:

Single post mounting with optional 4" and 8" Deck plate. Water resistant solenoid enclosure mounts to wall.

Integrated; Easy Service Strainer:

Patented integrated strainer enclosed in removable debris cup protects the solenoid valve and aerator from debris. Perforated stainless steel strainer is low maintenance and can be easily accessed.

Low Lead:

Complies with CA AB1953 and VT S152.

RECOMMENDED SPECIFICATION

Electronic Proximity Lavatory shall feature touch-free temperature control, vandal resistant all brass body with single inlet, built-in check valve, and in-line strainer. Shall also feature a low energy use electronically operated solenoid valve and microprocessor controlled proximity sensors. Shall meet ANSI A112.18.1M and ANSI 117.1 codes. Fitting shall be American Standard Model # 6058.____.

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

- ANSI A117.1**
- ASME A112.18.1**
- CSA B 125**
- NSF 61/Section 9**

 **MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES**

Other Aerators Available:

Part Suffix

- A15LV 1.5 gpm Anti-Microbial Vandal-Resistant Laminar Flow Outlet
- LV15 1.5 gpm Pressure Compensating Vandal-Resistant Laminar Flow Outlet
- V10 1.0 gpm Pressure Compensating Vandal-Resistant Aerator
- LV10 1.0 gpm Pressure Compensating Vandal-Resistant Laminar Flow Outlet

