## American Standard



### HAND HELD PERSONAL SHOWERS **& BODY SPRAYS**

	& BUDY SPRAYS					
Model #	Description/Features	Finishes	Roughing-In Dimensions			
1660.525	"Trevi" Personal Shower	.002 Polished Chrome	Dimensions			
	Self Cleaning Patented Design: Flexible ring with spray holes prevents lime scale build up.  Spray Pattern: Variable spray adjusts from a conventional spray to an aerated flow to a massage action.  Lightweight, Ergonomic Design: For a sure grip even with wet, soapy hands.  Flow Restrictor: 2.5 gpm/9.5L/min.	.020 White	160mm (6-1/4) 1/2" NPSM			
1660.500	"Soft" Personal Shower	.002 Polished Chrome				
1660.501	Spray Pattern: Variable spray adjusts from a conventional spray to a champagne flow.  Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the thumb. A true one-handed operation.  Lightweight, Ergonomic Design: For a sure grip even with wet, soapy hands.  Flow Restrictor: 2.5 gpm/9.5L/min.  "Sport" Personal Shower	.099 Polished Brass (PVD)	75mm (2-15/16) 175mm (6-7/8)			
	Spray Pattern: Conventional spray adjusts from an invigorating needle spray to a soft drenching flow.  Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the	.020 White .099 Polished Brass (PVD)	68mm (2-11/16) 160mm (6-5/16)			
	thumb. A true one-handed operation. <b>Lightweight, Ergonomic Design:</b> For a sure grip even with wet, soapy hands.		(0 3/10)			
	Flow Restrictor: 2.5 gpm/9.5L/min.		1/2" NPSM			
1660.503	"3" Function Personal Shower	.002 Polished Chrome				
	Spray Pattern: Variable spray adjusts from a conventional spray to an aerated flow to a massage action.  Simple Spray Pattern Adjustment: Spray patterns can be changed with a flick of the thumb. A true one-handed operation.	.020 Wille	73mm (2-7/8) 130mm (5-1/8)			
	<b>Lightweight, Ergonomic Design:</b> For a sure grip even with wet, soapy hands.					
	Flow Restrictor: 2.5 gpm/9.5L/min.		└_ 1/2" NPSM			

NOTE: Additional handshowers appear on back.

#### **SUGGESTED SPECIFICATION:**

Personal shower shall be ergonomically designed for a positive grip even when wet. Spray pattern adjustment (on applicable models) shall be performed with simple movement of thumb without need to change grip on handle. Fitting shall be American Standard Model # 1660.

# American Standard



## HAND HELD PERSONAL SHOWERS & BODY SPRAYS

	& BUDY SPRAYS					
Model #	Description/Features		Finish	es	Roughing-In Dimensions	
1660.504	Adjustable Personal Showe Spray Pattern: Conventional spra from an invigorating needle spray drenching flow. Simple Spray Pattern Adjustment patterns can be changed with a flict thumb. A true one-handed operation. Lightweight, Ergonomic Design sure grip even with wet, soapy hands.	y adjusts to a soft <b>nt:</b> Spray ck of the	.002 Polished Cl .020 White	nrome	73mm 2-7/8" 137mm (5-3/8)	
1660.505	Flow Restrictor: 2.5 gpm/9.5L/min. Fixed Personal Shower		.002 Polished Cl	nrome	- 1/2 TH SW	
	Spray Pattern: Fixed conventional split Lightweight, Ergonomic Designations are grip even with wet, soapy hands.  Flow Restrictor: 2.5 gpm/9.5L/min.	-	.020 White		67mm (2-5/8) 146mm (5-3/4)	
8888.035	59" (1500mm) Shower Hose Threads directly on 1/2" NPSM male personal hand held shower.		.002 Polished Chrome .020 White hreaded .099 Polished Brass			
1660.400	1/2" NPT In-Line Vacuum Br	eaker	.002 Polished Chrome			
	Attaches between supply outlet and shower hose.	personal .020 White .099 Polished Brass		ass (PVD)		
1660.120	"Sport" Deluxe Adjustable Body/Side Spray  Simple Spray Adjustment: Spray face adjusts up to 40° in any direction.  Flow Restrictor: 25gpm/9.5L/min.	.020 Wh	shed Chrome (1-1/2) FINISHED WALL (1-1/2) 38mm (1/2) MAX. 38mm(1/2) MAX. (4-3/4)			
1660.125	"Trevi" Deluxe Adjustable Body/Side Spray Self Cleaning Patented Design: Flexible ring with spray holes prevents lime scale build up. Spray Pattern: Variable spray adjusts from a conventional spray to a massage action. Simple Spray Adjustment:Spray position adjusts up to 20° in any direction. Flow Restrictor: 2.5 gpm/9.5L/min.	.002 Polis .020 Whit	shed Chrome te	38mm (1-1/2) ]	FINISHED WALL  2-1/4 (56mm) 40° DIA.  (75-89mm)	