

Product Specifications to	r ES92101
Job Name:	Job Type:
	71
Quantity:	Comments

108.	<b></b> 11
1911	Hillian
	ш.
-	W
	m
- 6	-

ES92101

**Carte 1-Light Pendant** 

Finish Glass/Shade **Product Category** Pendant System Satin Nickel

Other

Lamping Number of Bulb(s)	1	<i>Measurements</i> Width
Light Type	Incandescent	Height
Bulb Type	MB	Length
Max Bulb Wattage	100	Extension
Max Fixture Wattage	100	Back Plate Width
Rated Life	±2,500 Hours	Back Plate Height
Rated Lumens	±1,150	HCO
Color Temp	±2,700 K	Min Overall Height
Bulb(s) Included	No	Max Overall Height
Light Up/Down	N/A	Hanging Weight
Beam Spread	N/A	Height Adjustable
CRI	N/A	Slope
Photo Cell Included	N/A	Chain Length
Ballast/Driver/Transformer	No	Wire Length
Dimmable	Standard	Canopy Width
		Canopy Height

Measurements	
Vidth	4.00"
leight	3.00"
_ength	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
ICO	N/A
In Overall Height	N/A
Max Overall Height	60.00"
langing Weight	1.18 lb(s)
leight Adjustable	Yes
Slope	120°
Chain Length	N/A
Vire Length	120.00"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	1.25 lb(s)
Carton Width	6.00"
Carton Height	6.13"
Carton Length	6.25"
Carton Cubic Feet	N/A
Master Pack	12
Master Pack Weight	23.00 lb(s)
Master Pack Width	13.13"
Master Pack Height	20.25"
Master Pack Length	13.13"
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification	
Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Eq	uiva	lents

**UPC Code** 845094018407 Incandescent Watts N/A Material **Fluorescent Watts** N/A

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.