

# 12V LED/INCANDESCENT PATH & SPREAD

## RIBBED ROOF



**15418 AZT**

## TULIP



**15349 MST**

Ordering Guide & Finish	15418 AZT	15349 MST
Housing	Cast Aluminum with clear glass sprinkler shield	Aluminum
Lamp Base	12V T3 bi-pin, high temperature porcelain socket	12V S8 wedge base socket
Supplied Lamp	20-W(VA) T3 (17012) halogen Halogen light source Power usage at 12V AC input VA MAX: 20-W(VA)	18.5-W(VA) 3155K (15599 CLR) Krypton light source Power usage at 12V AC input VA MAX: 18.5-W(VA)
Incandescent Lamp Options	10-W(VA) T-3 (17011)	N/A
LED Lamp Options	2W (18042-18044) see page 137. Compares up to 20W Halogen.	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.
Wiring	20" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	37" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	8" In-ground slotted stake	8" In-ground slotted stake
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket
Integrated LED Options	N/A	N/A
Notes	N/A	N/A
Photometric with Supplied Lamp	Distance from Light	Distance from Light
	Foot Candles	Foot Candles