

SIDE MOUNT  
ECLIPSE™



15423 AZT, BKT

DOME



15310 AZT, AZT6, BKT

Ordering Guide & Finish	15423 AZT 15423 BKT									15310 AZT 15310 AZT6 15310 BKT										
Housing	Cast Aluminum									Cast Aluminum										
Lamp Base	12V S8 wedge base socket									12V T5 wedge base socket										
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)									16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)										
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)									11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)										
LED Lamp Options	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.				2W (18122-18123) see page 138. Compares up to 18.5W Krypton.					2W (18039-18041) see page 137. Compares up to 16W Xenon.										
Wiring	34" of usable #18-2, SPT-1-W leads. Cable connectors supplied.									24" of usable #18-2, SPT-1-W leads. Cable connectors supplied.										
Mounting Access. (Included)	8" In-ground slotted stake									8" In-ground slotted stake										
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket									15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket										
Integrated LED Options	N/A									15810 – on Page 42										
Notes	N/A									Coordinates with our 15410 & 15470 Domed Roof series.										
Photometric with Supplied Lamp	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'
	Foot Candles	8.7	3.3	1.1	.4	.1	-	-	-	-	Foot Candles	8	4.1	1.6	.5	.4	.1	-	-	-