

### Product Information

Applicable product:				
Bath whirlpool with Massage Experience			K-1110-M	
Fixture:*				
Bathing well:				
Basin area, bottom		42" (106.7 cm) x 25-1/2" (64.8 cm)		
Basin area, top		63" (160 cm) x 31-1/2" (80 cm)		
Weight		160 lbs (72.6 kg)		
To overflow:				
Water depth to rim		19-1/4" (48.9 cm)		
Capacity		96 gal (363.4 L)		
* Approximate measurements for comparison only.				
Included component:				
Cut-out template			1016369-7	
Pump	Heater	V	Hz	A
	1.5 kW	240	50/60	15

Required accessories:

Clearflo horizontal overflow bath drain K-7273

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control 220/240 V, 20 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Pump/piping protrudes beyond rim (see below).

Floor support under whirlpool must provide a minimum of 43 lbs/square foot (209 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain shown. (K-7273)

**Note:** Pump/Piping Protrudes Beyond Rim

