

Product Information

Applicable products:	
Bath whirlpool with integral flange and heater – left drain	K-1114-LH
Bath whirlpool with integral flange and heater – right drain	K-1114-RH

Fixture*:	
Bathing well:	
Basin area, bottom	55" (139.7 cm) X 23-1/4" (59.1 cm)
Basin area, top	64" (162.6 cm) X 32" (81.3 cm)
Weight	110 lbs (50 kg)
To overflow:	
Water depth	15" (38.1 cm)
Capacity	57 gal (215.9 L)
* Approximate measurements for comparison only.	

Drop-in cut-out dimensions:	
58-1/2" (148.6 cm) x 40-1/2" (102.9 cm)	

Pump:	V	Hz	A
1-speed	120	60	7.5
Heater:	kW	V	Hz
	1.5	120	60
			A
			12.5

Minimum access panel pump/control:	
20" (50.8 cm) W x 15" (38.1 cm) H	required

**Required Electrical Service
(2 required)**

Two dedicated circuits required, both protected with a Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump and, if supplied, heater.	

Installation Notes

Install this product according to the installation guide.

Floor support under the whirlpool must provide for a minimum of 30 lbs/square foot (142 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

WINDWARD®

