

KOHLER®

Roughing-In

K-1110
PURIST®
BATH WHIRLPOOL

Product Information

| | |
|---|------------------------------------|
| Applicable product: | |
| Bath whirlpool | K-1110 |
| Fixture*: | |
| Bathing well: | |
| Basin area, bottom | 45" (114.3 cm) x 25-1/2" (64.8 cm) |
| Basin area, top | 63" (160 cm) x 31-1/2" (80 cm) |
| Weight | 160 lbs (72.6 kg) |
| To overflow: | |
| Water depth to rim | 21" (53.3 cm) |
| Capacity | 115 gal (435.3 L) |
| * Approximate measurements for comparison only. | |
| Required accessories: | |
| Template kit (undermount only) | K-589 |
| Clearflo horizontal overflow bath drain | K-7273 |
| Jet trim kit | K-9698 |

| | | | | |
|---------------------------------|--------|-----|-----------|----|
| Included components: | | | | |
| Cut-out template (drop-in only) | | | 1016369-7 | |
| Pump | Heater | V | Hz | A |
| | 1.5 kW | 240 | 50/60 | 15 |

Required Electrical Service

| | |
|--|---------------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD): | |
| Pump/control | 220/240 V, 20 A, 50/60 Hz |

Installation Notes

Install this product according to the installation guide.

Pump/piping protrudes beyond rim (see below).

Floor support under whirlpool must provide a minimum of 50 lbs/square foot (243 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain shown. (K-7273)

