

KOHLER® Roughing-In

K-1139, K-1139-L, K-1139-R
PROFLEX® 6036
BATH WHIRLPOOL

Product Information

Applicable products:	
Bath whirlpool – drop-in	K-1139
Bath whirlpool – tile flange, left drain	K-1139-L
Bath whirlpool – tile flange, right drain	K-1139-R

Fixture*:	
Basin area:	
Bathing well	46" (116.8 cm) x 15" (38.1 cm)
Top area	55" (139.7 cm) x 25" (63.5 cm)
Weight	55 lbs (25 kg)
To overflow	
Water depth	14" (35.6 cm)
Capacity	57 gal (216 L)
* Approximate measurements for comparison only.	

Drop-in cutout	58-1/2" (148.6 cm) x 34-1/2" (87.6 cm)
----------------	--

Pump:	V	Hz	A
1-speed	120	60	7.5

Minimum access panel (required):	20" (50.8 cm) x 15" (38.1 cm)
----------------------------------	-------------------------------

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (180.9 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677)

