

Product Information

Applicable product:			
Bath whirlpool		K-1221	
Fixture*:			
Bathing well:			
Basin area, bottom	47" (119.4 cm) x 37" (94 cm)		
Basin area, top	67" (170.2 cm) x 42" (106.7 cm)		
Weight	120 lbs (54.4 kg)		
To overflow:			
Water depth	16-7/8" (42.9 cm)		
Capacity	122 gal (461.8 L)		
* Approximate measurements for comparison only.			
Drop-in cut-out		70-1/4" (178.4 cm) x 46-1/4" (117.5 cm)	
Pump:			
1-speed	V	Hz	A
	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 49 lbs/square foot (236.6 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

