

KOHLER® Roughing-In

K-1849-H2 UNDERScore® BATH WHIRLPOOL WITH HEATER

Product Information

Applicable product:				
Bath whirlpool with heater		K-1849-H2		
Fixture*:				
Bathing well:				
Basin area, bottom	39-9/16" (1005 mm) x 24-11/16" (627 mm)			
Basin area, top	53-5/8" (1362 mm) x 29-1/2" (749 mm)			
Weight	125 lbs (56.7 kg)			
To overflow:				
Water depth	17-1/8" (435 mm)			
Capacity	81.1 gal (307 L)			
* Approximate measurements for comparison only.				
Drop-in cut-out	59-1/2" (1511 mm) x 35-1/2" (902 mm)			
Pump	kW	V	Hz	A
Variable-speed	1.5	240	50/60	11

Required accessories:

Clearflo slotted overflow brass bath drain OR	K-7271
Clearflo slotted overflow bath drain – PVC pipe	K-7272
Jet trim kit	K-9698

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control: 220-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 56 lbs/square foot (273 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standards Z124.1.2. All dimensions are nominal.

