

Product Information

Applicable product:				
5.5' Relax Experience bath whirlpool		K-1457-CT		
Fixture*:				
Bathing well:				
Basin area, bottom	50" (127 cm) x 29" (73.7 cm)			
Basin area, top	61" (154.9 cm) x 32" (81.3 cm)			
Weight	130 lbs (59 kg)			
To overflow:				
Water depth	16" (40.6 cm)			
Capacity	100 gal (378.5 L)			
* Approximate measurements for comparison only.				
Included components:				
Cut-out template		113311-7		
Pump	Heater	V	Hz	A
	1.5 kW	240	50/60	11
Minimum access panel (required):				
Pump/control	34" (86.4 cm) W x 15" (38.1 cm) H			

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control	220-240 V, 20 A, 50/60 Hz
--------------	---------------------------

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 51 lbs/square (248 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

Recommended Faucet Area

The pump and piping protrude beyond the rim.

