

KOHLER® Roughing-In

K-4396
ANGLESEY™
BOWL

Product Information

Applicable product:	
Elongated bowl toilet	K-4396
Elongated bowl toilet with bedpan lugs	K-4396-L
Fixture:	
Configuration	Rear spud, elongated
Water per flush	1.6 gal (6 L)*
Spud size	1-1/2"
Passageway	2-3/8" (60 mm)
Water area	11" (279 mm) x 9-1/2" (241 mm)
Water depth from rim	5-1/4" (133 mm)
Seat post hole centers	5-1/2" (140 mm)
Minimum static pressure required	35 psi (241.3 kPa)
Maximum static pressure	80 psi (551.6 kPa)
Minimum flowing pressure required	25 psi (172.4 kPa)
Required supply minimum	25 gpm (94.6 lpm)
* Designed to flush with 1.6 gal (6 L) of water when installed with a 1.6 gpf (6 lpf) valve.	

Recommended accessories:	
Lustra™ open front seat	K-4670-C
Lustra™ open front seat with anti-microbial agent	K-4670-CA
Floor bolts (pair)	21401

Included components:	
Spud	18357
Bolt caps (pair)	52048
Floor screws (pair)	21402

Installation Notes

Install this product according to the installation guide.

Refer to manufacturer and local codes for flush valve requirements.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** Barrier Free requirements when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

