

Product Information

Applicable faucet trim only:	
Bath and shower standard handle*	K-T6908-2A
Bath and shower lever handle*	K-T6908-4A
Shower standard handle*	K-T6910-2A
Shower lever handle*	K-T6910-4A
Valve standard handle*	K-T6913-2
Valve lever handle*	K-T6913-4
*Rite-Temp® valve must be ordered to complete faucet.	

Required accessories:	
Rite-Temp valve OR	K-304-*
HiFlow Rite-Temp valve with stops	K-2971-KS
* For a complete listing of all the Rite-Temp valves, refer to the K-304-* Specification Sheet or Roughing-In sheet.	

Optional accessories:	
Deep roughing-in kit for Rite-Temp® valve (lever handles)	58223
Deep roughing-in kit for Rite-Temp® valve (standard handles)	58229
HiFlow Rite-Temp® thin wall installation kit	88526

Installation Notes

Install this product according to the installation guide.

NOTICE: Risk of product damage. Long screws, for installing trim, can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Avoid cross-flow conditions. Do not install shut-off device on either valve outlet.

Cap shower outlet if deck-mount spout, diverter, or handshower is connected to spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between valve and wall-mount spout.

