

Product Information

Applicable product:	
Bath – airjet trim/White	K-899-GC0
Bath – airjet trim/Almond	K-899-GC47
Bath – airjet trim/Biscuit	K-899-GC96
Bath – airjet trim/Polished Chrome	K-899-GCCP
Bath – airjet trim/Brushed Nickel	K-899-GCBN
Bath – airjet trim/Vibrant Polished Nickel	K-899-GCSN
Bath – airjet trim/Dune	K-899-GCNY

Fixture*:	
Bathing well:	
Basin area, bottom	49" (1245 mm) x 26-1/2" (673 mm)
Basin area, top	62-1/2" (1588 mm) x 29-1/4" (743 mm)
Weight	435 lbs (197.3 kg)
To overflow:	
Water depth	19" (483 mm)
Capacity	90 gal (340.6 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	66-1/2" (1689 mm) x 35-1/2" (902 mm)
-----------------	--------------------------------------

Blower motor:	kW	V	Hz	A
	300	220-240	50/60	3

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Blower motor/control	220-240 V, 15 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

NOTICE: If the blower motor and check valve are relocated, two access panels are required. Locate one access panel at the blower motor/control location and the other at the control box. Locate the blower motor and check valve together.

Floor support under bath must provide for a minimum of 78 lbs/square foot (386 kg/square meter) loading.

Splitting the deck/surround is recommended if installing into a deck.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7272)

