

Product Information

Applicable product:	
Comfort Height toilet - left trip lever (shown)	K-3828
Comfort Height toilet - right trip lever	K-3828-RA
Fixture:	
Configuration	one-piece, elongated
Water per flush	1.28 gpf (4.8 lfp)
Passageway	2-1/8" (54 mm)
Water area	11-3/4" (298 mm) x 8" (203 mm)
Water depth from rim	6-1/8" (155 mm)
Seat post hole centers	5-1/2" (140 mm)

Included components:	
Tank cover	1036367
Trip lever, left-hand OR	K-9466-L
Trip lever, right-hand	K-9466-R
Toilet seat	K-4636
Tank accessory pack	52265
Bolt cap accessory pack	1013092

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (**ADA**) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

