

Product Information

Applicable product:	
5' VibrAcoustic bath with integral apron, left drain (shown)	K-1151-VBLA
5' VibrAcoustic Bath with integral apron, right drain	K-1151-VBRA

Fixture*:	
Bathing well:	
Basin area	45" (1143 mm) x 22" (559 mm)
Top area	54" (1372 mm) x 25" (635 mm)
Bath with apron	
Weight	91 lbs (41.3 kg)
To overflow:	
Water depth	15" (381 mm)
Capacity	60 gal (227.1 L)
*Approximate measurements for comparison only.	

Amplifier/control:	Power per channel (rms) W	V	Hz
	15	120	50/60z

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Amplifier/control:	120 V, 15 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.
 Control amplifier fits 16" (406 mm) center studs.
 A grounded outlet within the wall framing must be within 24" (610 mm) of the planned control amplifier.
 Cables are included, 25' (7.6 m) each.
 Floor support under bath must provide for a minimum of 45 lbs/square foot (219.7 kg/square meter) loading.
 Ensure that the bath, user interface, amplifier, and transducers are functional before completing the installation.
 Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

