

Kwikset UltraMax Security Levers Specifications

Kwikset UltraMax Security Lever Specifications

| | |
|-----------------------|---|
| Door Prep | Crossbore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4" |
| Backset | 2-3/8" standard on interiors. Adjustable 2-3/8" or 2-3/4" standard on entry. UL 2-3/4" standard. 2-3/8" optional. |
| Door Thickness | 1-3/8" – 1-3/4" doors standard. 2-1/4" doors optional on 720 and 740 models. |
| Cylinder | 6-pin removable core. |
| Faceplates | 1" x 2-1/4" square corner standard. Round corner and other options available. |
| Strikes | 2-1/4" full lip square corner standard. Round corner and other options available. |
| Bolt | 1/2" throw. Nickel plated. |
| Door Handing | Specify handing when ordering all levers as interior trim for exterior doors. |
| ANSI/BHMA | A156.2 Grade 2. |

Kwikset UltraMax Security Lever Dimensions

| Dimensions | Design | A | B | C |
|------------|--------------|--------|---------|----------|
| | Brooklane | 2-5/8" | 4-3/16" | 2-3/16" |
| | Commonwealth | 2-5/8" | 3-5/8" | 1-15/16" |

Kwikset UltraMax Security Lever Finishes

| Design | L03 | 3 | 5 | 10B | 15 | 15A | 26 | 26D |
|--------------|-----|---|---|-----|----|-----|----|-----|
| Brooklane | • | • | • | • | • | • | • | • |
| Commonwealth | • | • | • | • | • | • | • | • |

Kwikset UltraMax Security Lever Dimensions

| Function | Model | Description |
|----------|--------------------------|--|
| | 720 <i>F75</i> | Passage/Hall & Closet: Both levers always free. |
| | 730 <i>F76</i> | Privacy/Bed & Bath: Both levers locked or unlocked by turnbutton inside. Outside lever unlocked by emergency key. |
| | 740 <i>F81</i> | Keyed Entry Lever: Outside locked or unlocked by key outside or turnbutton inside. |
| | 788 | Half Dummy Trim, Surface mounted: For doors where only a pull is required. No operation. |

Note: ANSI functions are listed in italics.

