

## PF1600 Series

# Rear Outlet Toilet Pressure Assist - 1.0 gpf



### Product Features

- Two-piece vitreous china
- Floor mount back outlet bowl
- Available in Round Front, Elongated and ADA floor mount back outlet bowls
- 1.0 gpf HET, High Efficiency Toilet with Pressure Assist
- Equipped with Sloan Flushmate IV System
- 2" fully glazed trapway
- Siphon Jet Technology
- EPA WaterSense Certified
- Large 12-1/4" x 9-5/8" water surface
- 4-1/4" rough-in
- Close coupled tank with cover
- Available in white only
- Seat and supply not included
- Uses 35% less water than standard (1.6 gpf) low consumption toilets




PF1605PAWH/PF1612PAWH

### Available Parts

- FC100500K** Replacement cartridge for 1612 tank  
**FBL100504K** Lower supply kit  
**FBU100505K** Upper supply kit  
**FE205288** Tank to Bowl Gasket  
**PF129837** Flush handle and rod for LH tank  
**PF129838** Flush handle and rod for RH tank  
**PF1612PALIDWH** Replacement lid

Technical Information	
Configuration	two-piece toilet
Water per flush	1.0 gpf/3.8 lpf
Trapway	2" fully glazed
Water area	12-1/4" X 9-5/8"
Seat post hole centers	5 1/2"

Specified Model	Model Description	Color Finishes
* PF1604PAWH	1.0 gpf round back outlet bowl	○ White (WH)
* PF1605PAWH	1.0 gpf elongated back outlet bowl	○ White (WH)
 PF1606PAWH	1.0 gpf ADA height back outlet bowl	○ White (WH)
PF1612PAWH	1.0 gpf Pressure Assist tank white	○ White (WH)
PF1612PALWH	1.0 gpf Pressure Assist tank with locking lid	○ White (WH)
PF1612PARWH	1.0 gpf Pressure Assist tank white with Rh trip lever	○ White (WH)

\* = complies with CSA B651

 = complies with ADA & CSA B651

### Codes and Standards

Meets strict flushing performance guidelines established by the EPA (Environmental Protection Agency) WaterSense program. Leadership in Energy and Environmental Design (LEED) Compliant. Los Angeles Department of Water and Power (LADWP) Compliant. IAPMO/UPC, ASME A112.19.2M, CSA B651



