CODER PL SERIES FLAT DOOR CABINET


Features

- Recess or surface mount
- Mirrored doors and interior
- 3-way adjustable concealed hinge system
- SAFESEAL™ gasket frame
- Rust-free aluminum construction
- Can be installed as a left- or right-hand door swing
- Three adjustable glass shelves
- 23-1/4" (59.1 cm) x 30" (76.2 cm) x 4-5/8" (11.7 cm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

None applicable



PLM2430W

Specified Model

Model	Description			
PLM2430W	Plain edge, white interior			
PLM2430B	430B Plain edge, black interior			
PLM2430WB	LM2430WB Beveled edge, white interior			
PLM2430BB	Beveled edge, black interior			
NOTE: No addit	ional hardware is required for installing cabinets side-by-side.			
Required Accessories - For Surface-Mount Installations Only				
M30SKD4A	Aluminum side kit			
PLSK30	Mirrored side kit			
Refer to the Price	e Guide for additional side kit colors and finishes	·		
Optional Acces	sories			
SLB24D4	Safety-lock box			
	Black swing-out magnifying mirror			
SOMM	Diack Swing-out magnifying minor			

PL SERIES FLAT DOOR CABINET

Technical Information

Roughing-in opening	22-1/2″ (57.2 cm) x 29-1/4″ (74.3 cm) x 4″ (10.2 cm)
Door opening angle	170°

Installation Notes

Install this product according to the installation guide.

When determining the height of the mirrored cabinet, ensure the mirrored door will clear all obstacles, such as a faucet. A minimum distance of 1" (2.5 cm) is required.

Secure the screws (provided) to a stud to avoid possible property and product damage. If this is not possible, anchors (provided) must be inserted before installing the screws.

Modular components can be joined horizontally. When ganging cabinets: rough opening width/height = total width/height of all cabinets and lights minus 3/4" (1.9 cm).

Recessed cabinets project 7/8" (2.2 cm) from wall.

