

ECONOMY & COMMERCIAL

S-2220-AF



S-2270-AF



S-2271-AF



S-2292-AF



S-2291-AF



S-2288-AF



S-2460-AF



S-2280-AF



S-2285-AF



Showerheads GENERAL SPECIFICATION

ECONOMY

Polished chrome plated. Chrome plated shank. Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1 Standard.

S-2220-AF

Adjusta-Spray showerhead. Brass ball swivel joint. Spray adjusting T-handle. 2-1/2" face. 40 spray slots at various angles for complete coverage. 1/2" NPT inlet.

S-2270-AF

Cosmopolitan showerhead. Chrome plated brass ball joint. 2" fully adjustable black spray face. 1/2" NPT inlet.

S-2271-AF

Cosmopolitan showerhead. Adjustable ball joint. 2" fully adjustable black spray face. 1/2" NPSM inlet with sealing washer.

S-2291-AF

2-1/2" brass shank. Spray adjusting T-handle. Brass ball swivel joint.

S-2292-AF

1-3/4" brass shank. Spray adjusting T-handle. Sealing washer. Brass ball swivel joint.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BP	Blister Pack Packaging

COMMERCIAL BRASS SHOWERHEADS

Polished chrome plated. Water conserving pressure compensating Autoflo® device reduces flow to a maximum of 2.5 gpm/9.46 lpm, to meet existing ANSI A112.18.1 Standard. Vandal-resistant standard. 1/2" NPT back inlet.

S-2288-AF

Watersaver showerhead. Brass shank. Brass adjustable spray face. Brass ball swivel joint.

S-2460-AF

Solid brass Adjusta-Spray wall mounted showerhead. 2" face. 60 spray channels at three different angles to allow a full coverage shower. Drilled for, but less mounting bolts.

S-2280-AF

Anystream wall mounted showerhead. Rigid brass ball. Spray adjusting T-handle 2-1/2" face. 4 Lexan® deposit resisting plungers with 32 spray channels. Drilled for, but less mounting bolts.

S-2285-AF

Watersaver showerhead. Rigid brass head. Adjustable spray. Drilled for, but less mounting bolts.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> AP	Anchor Plate Assembly with Mounting Screws (not S-2288-AF)
<input type="checkbox"/> BJ	Ball Joint (S-2280, S-2285 only)
<input type="checkbox"/> BPT	1/2" British pipe thread inlet (S-2288-AF only)
<input type="checkbox"/> 2	S-2252-AF Anystream Showerhead (S-2280 only)

This space for Architect/Engineer approval.

