

INSTALLATION INSTRUCTIONS

Item #8609-PL Rev. 05/10/2012

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig.1)

1. Shut off power at the circuit breaker and remove old fixture from ceiling, including the crossbar.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Attach the Crossbar (A) to the Junction Box using the two Screws (B) from the outlet box. The side of the Crossbar marked "GND" must face out.
4. Thread the Nipple (C) part way into the center hole of the Crossbar.

CONNECTING THE WIRES (Fig.2)

5. While holding the Ceiling Pan towards the ceiling, connect the electrical wires as shown in (Fig.2), making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's Ground Wire to it. Otherwise, connect the fixture's Ground Wire directly to the Crossbar using the Green Screw provided.
6. After wires are connected, tuck them carefully inside the junction box as you hold the Ceiling Pan (D) assembly toward the ceiling.

FINISHING THE INSTALLATION (Fig. 1)

7. Finish mounting the Ceiling Pan (D) by placing it over Nipple (C) so that it protrude through the hole in the ceiling Pan (D). Secure the Ceiling Pan against the ceiling with the Decorative Knob (E).
8. Install the PL bulb (H) (included) into socket (I) in accordance with the fixture's specification. **(DO NOT EXCEED THE SPECIFIED WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
9. The ballast and lamp are combined, to replace or install, twist pins into socket as shown on Fig 3.
10. Finish mounting the fixture by aligning the holes on the top of the Glass Shade (F) with the tapped holes on the Ceiling Pan (D) and secure the Glass Shade (F) by threading two Mounting Screws (G) into the tapped holes.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Warning: When relamping, please use UL and CUL Listed Self-Ballast Fluorescent Lamp, certificated by UL1993.

