

To be specified for top spud fixtures with exposed valves:

### Urinal Flush Valve

- TMU1LN#CP - Valve Only, 0.5 GPF/1.9 LPF
- TMU1LN12#CP (3/4" V.B.) - Complete Set, 0.5 GPF/1.9 LPF
- TMU1LN22#CP (1-1/4" V.B.) - Complete Set, 0.5 GPF/1.9 LPF

Complete Set Supplied With:

- Vacuum Breaker & Angle Stop Set – VB9CP-12
  - 3/4" Angle Stop – 10077t4
  - 3/4" Vacuum Breaker – 10075t2
  - Spud Nut & Escutcheon – 71051Nt5
  - Sweat Solder Kit – TH559EDVJSJ
- Vacuum Breaker & Angle Stop Set – VB9CP-22
  - 3/4" Angle Stop – 10077t4
  - 1-1/4" Vacuum Breaker – 10075t5
  - Spud Nut & Escutcheon – 71051Nt7
  - Sweat Solder Kit – TH559EDVJSJ

Z-4000-J - Adapter for Ground Joint Angle Stops

*Meets the American with Disabilities Act Guidelines and ANSI A117.1 requirements for people with disabilities*



TMU1LN12#CP

## FLUSHOMETER VALVE

TOTO's® superior quality manual flushometer valves incorporate a durable bronze body with a nickel-chrome finish and an adjustable tailpiece. Also featured is a flush lever with a triple sealing structure to prevent leaks and a stainless steel collar to reduce sticking, even under severe water conditions. TOTO® flushometer valve accessories include: a check valve angle stop with threaded vandal resistant cap, vacuum breaker outlet tube, wall flange with sweat solder kit, fixture spud nut and escutcheon.

## SUPERIOR PISTON VALVE TECHNOLOGY

TOTO's® piston valve technology is a marked improvement over traditional rubber diaphragm type valves. Not only does the longer piston travel and self-cleaning, debris screen reduce common problems such as continuous running and flooding, but the piston itself will not warp or mis-seal, thus significantly reducing repair and maintenance costs. A micro-porous cup seal keeps the piston self-lubricated with the incoming water supply upon each activation.

## STANDARD OF PERFORMANCE

A superior and unparalleled engineering design assures a consistently strong flushing action even under a wide range of water pressure.



# Manual Urinal Flushometer Valve HEU Exposed – 0.5 GPF

## SPECIFICATIONS

<b>Product</b>	TMU1LN#CP - Valve Only, 0.5 GPF/1.9 LPF, Right/Left Hand Rough TMU1LN12#CP - Complete Set (3/4" V.B.), 0.5 GPF/1.9 LPF, Right/Left Hand Rough TMU1LN22#CP - Complete Set (1 1/4" V.B.), 0.5 GPF/1.9 LPF, Right/Left Hand Rough
<b>Fixture Type</b>	Low consumption urinal 0.5 GPF/1.9LPF flushometer type.
<b>Water supply pipe</b>	3/4" NPT
<b>Water supply pressure</b>	15 psi - 100 psi *
<b>Listings</b>	 A.S.S.E. 1037
<b>Warranty</b>	Limited three (3) year warranty on all component parts. Details available upon request.

*These dimensions and specifications are subject to change without notice.*



*\*Water pressures over 80 psi are not recommended for most plumbing fixtures.*

## SUGGESTED ENGINEERING SPECIFICATION:

TOTO® Model No. \_\_\_\_\_  
Manual type urinal flushometer valve, non-hold-open piston type with, self-cleaning debris screen and precise flushing capability. Low consumption 0.5 GPF/1.9 LPF model. Valve

to deliver precise flush volume from 15-100 psi. Accessories to include angle stop with check valve, vacuum breaker. Sweat solder kit, spud nut and escutcheon.

## DIAGRAM:



**TOTO®**

TOTO® U.S.A., INC. • 1155 Southern Road, Morrow, GA 30260

Tel. (888) 295-8134 • Fax. (800) 699-4889 • www.totousa.com

Printed in U.S.A. © TOTO® U.S.A. 08/08 #H80012

Printed on recycled paper 

REV 08/08