

THIS SPACE FOR DESIGNER/ ENGINEER APPROVAL

Job/Customer _____ Date _____ Contractor _____

Model Specified _____ Qty _____ Approved By _____

Designer/Engineer _____ Date _____ Contractor's PO# _____


Submitted by _____ Date _____ Other _____

4172 Series FULL PORT FORGED BRASS BALL VALVES 1/4" THREADED GAUGE HOLE (PLUGGED) W/ REVERSIBLE HANDLE IPS 600 WOG / 150 WSP

ITEM #	SIZE	P/CARTON	P/CASE	A	B	C	D	E	Cv
41722	1/2"	10	80	1/2	2 5/16	2 1/16	3 7/16	1/4	11.5
41723	3/4"	10	60	3/4	2 11/16	2 5/16	3 1/2	1/4	27.1
41724	1"	6	48	1	3	2 1/2	4 5/16	1/4	49.3
41725	1 1/4"	4	32	1 1/4	3 3/4	3 1/8	5 1/8	1/4	114.1
41726	1 1/2"	2	24	1 1/2	4 1/8	3 11/16	5 3/8	1/4	161.3
41727	2"	2	16	2	4 5/8	4 1/8	6 1/2	1/4	248.7



NO.	DESCRIPTION	MATERIAL
1	BODY	BRASS
2	END CAP	BRASS
3	SEAT	PTFE
4	BALL	BRASS HCP
5	STEM	BRASS
6	PACKING GLAND	BRASS
7	STEM SEAL	PTFE
8	HANDLE	STEEL CP
9	HANDLE NUT	STEEL CP
10	HANDLE JACKET	VINYL
11	GAUGE HOLE NUT	BRASS
12	WASHER	FIBER



TEMP °F	WOG
100	600
150	490
200	470
250	439
300	411
350	294
366	N/A

Specifications: Designed for residential, commercial or industrial use with water, oil or gas. This approved Webstone Valve is actuated by a blowout proof stem and features an adjustable packing gland. Threaded ends comply with ANSI B1.20.1

Webstone Company, Inc.
www.webstonevalves.com

Quality and Commitment Since 1954

Tel: (800) 225-9529 • Fax (800) 336-5133

Webstone product specifications in U.S. customary units are approximate and are provided for reference only. Webstone reserves the right to change or modify product design, construction, specifications or materials without prior notice and without incurring any obligation to make such changes and modifications on Webstone products previously or subsequently sold.

4172spec_101909