Product Name:	ABT-AFPP-49
Description:	· · · · · · · · · · · · · · · · · · ·
	49 Cu. Ft. Capacity
	Two solid stainless steel swing doors
	Multi-Point temperature mapping via NIST traceable data acquisition,
	15 probes in air and 3 probes in sample solution for 360 minutes with
	temperature readings every 60 seconds
	Temperature Display & Alarm Module:
	Microprocessor Temperature Controller
	Adjustable operating temperature range: -15°-25°C
	Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution
	Adjustable temperature display in Celsius or Fahrenheit
	Audible and visual high/low temperature alarms
	Sensor error alarm
	Power failure alarm
	Resettable 1-point Min/Max History
	Remote alarm contacts
	Alarm validation (audible, visual, and remote alarm)
	Alarm mute with ring back
	Six shelves (adjustable in ½" increments)
	Keyed door locks
	Magnetic door gasket for positive seal
	Recessed door handles
	Swivel casters (adds 5" to height; included in dimensions)
	Interior light
	Probe access port (3/8")
	300 Series stainless steel interior/exterior
	High density urethane foam cabinet and door insulation HFC-free refrigerant (R290a), foam insulation and packaging
	Quality certified with 100% unit temperature testing
	Two year parts and labor warranty, plus an additional three year
	compressor parts warranty
	Exterior dimensions: 54 1/8" W x 31 5/8" D x 78 5/16" H without
	casters; 83 5/16" H with casters
	Auto defrost
	115V, 60 Hz, 11 Amps,3/4 HP
	UL/C-UL listed
	Shipping weight: 550 lbs.
	