



Job Name:

Job Type:

Comments:

Quantity:

**Product Number: 1207QC**

**Dimensions:**

**Diameter:** 4 1/4"

**Switch Type:** N/A

**Length:** 13 1/2"

**Mounting Proc.:** Other

**Width:** 5 1/4"

**Height:** 5 5/8"



#### 1207QC - Non-IC 4" Housing wiht "Quick Connects"

Mini-Recessed Non-IC Housing with Quick Connects

Trims: 1232AT, 1238AT, 12040AT, 12041AT, 1242AT, 1226AT, 1236AT, 1237AT, 1239AT

Safe- Thermally Protected: Thermal protector safeguards against overheating caused by improper insulating and overlamping.

Safe- Listed for Damp Location: Listed for use where insulation is kept at least 3" away from housing.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Bar Hanger Locking Tabs: Squeeze tabs with pliers to lock bar hangers in place.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Trouble-Free Transformer: Provided with integral magnetic transformer offering years of trouble-free operation.

Time-Saving Junction Box Design: Junction box saves installation time with snap-on overs, pry-out knock-outs, riveted ground wire, and through-circuit wiring, with 4-in-4 out #12 wires.

Easy Access Housing: Housing removable for easy access to junction box.

**UPC #:** 785652012075

**Product Type:** Recessed  
Light

#### Features:

Title 24

#### Bulbs:

- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included
- 1 - GU5.3 Bi-Pin Halogen MR16 50w max 120v - Not included

#### Material List:

- 1 Housing - Steel - Raw Steel

#### Instruction Sheets

- English (HC-675)

## Trim



### 12040AT-15

#### **4" Wall Wash Trim**

White Steel Baffle  
 White Aluminum Reflector  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 12041AT-15

#### **4" Shower Trim**

Frosted Glass Glass  
 White Aluminum Reflector  
 White Aluminum Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16  
 Suitable For Shower Light



### 1226AT-14

#### **4" Baffle Trim**

White Trim / Baffle Steel Baffle  
 White Trim / Baffle Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1226AT-15

#### **4" Baffle Trim**

Black Steel Baffle  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1232AT-14

#### **4" Multiplier Trim**

White Trim / Baffle Aluminum  
 Reflector  
 White Trim / Baffle Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1232AT-172

#### **4" Multiplier Trim**

Antique Bronze - White  
 Aluminum Reflector  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1232AT-22

#### **4" Multiplier Trim**

Polished Aluminum Aluminum  
 Reflector  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1232AT-71

#### **4" Multiplier Trim**

Antique Bronze Aluminum  
 Reflector  
 Antique Bronze Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1232AT-849

#### **4" Multiplier Trim**

Satin Nickel Aluminum  
 Reflector  
 Satin Nickel Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1232AT-861

#### **4" Multiplier Trim**

Satin Nickel - White Aluminum  
 Reflector  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1236AT-15

#### **4" Eyeball Trim**

White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1237AT-15

#### **4" Adjustable Eyeball Trim**

White  
 Clear Glass Lens  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1238AT-15

#### **4" Pin Hole Trim**

White Aluminum Reflector  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1239AT-15

#### **4" Slot Aperture Trim**

Clear Glass Lens  
 White Steel Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16



### 1242AT-15

#### **4" Shower Trim**

Frosted Glass Glass  
 White Aluminum Trim  
 Maximum Wattage:  
 50w Halogen MR16  
 50w Halogen MR16  
 Suitable For Shower Light

Replacement Bulb Data:											
Product #			Type	Base	Watts	Watts Consumed	Volts	Hours	Lumens	Temp (°K)	CRI
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	
9709	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	12 NSP 12°	3000	
9711	Clear Glass Lens	Halogen	Halogen MR16	GU5.3 Bi-Pin	50	50	12v	2000	40 FL 38°	3000	

Shipping Information									
Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652012075	15	7.5	6	0.391	3.9	Yes	C IP-3
Master Pack	6	10785652012072	21	20.5	6.75	1.682	25.6	Yes	A M-1