



Description:

The Rainbow II wall sconce may be mounted as an up-light or a down-light. The wall sconce may be mounted as a square or at an 45 degree angle to create a diamond shape. The metal canopy and stem is available in bronze. A 75W dimmable electronic transformer is included on the mounting plate.

Part Numbers:

101725bz	bronze, orange glass
101725ch	chrome, orange glass
101725mc	matte chrome, orange glass
101726bz	bronze, smoky glass
101726ch	chrome, smoky glass
101726mc	matte chrome, smoky glass
101728bz	bronze, turquoise glass
101728ch	chrome, turquoise glass
101728mc	matte chrome, turquoise glass
101729bz	bronze, red glass
101729ch	chrome, red glass
101729mc	matte chrome, red glass
101816bz	bronze, retro white glass
101816ch	chrome, retro white glass
101816mc	matte chrome, retro white glass
101817bz	bronze, retro black glass
101817ch	chrome, retro black glass
101817mc	matte chrome, retro black glass
101916bz	bronze, dichroic rainbow glass
101918ch	chrome, dichroic rainbow glass
101918mc	matte chrome, dichroic rainbow glass
101919bz	bronze, dichroic sunrise glass
101919ch	chrome, dichroic sunrise glass
101919mc	matte chrome, dichroic sunrise glass

Technical Specs:

120V AC, 50/60Hz input
 11.7V AC output
 50VA, 49W for 1(maximum 50 Watt lamp)
 GY6.35 socket
 Suitable for dry locations only
 Mount to 3 1/2" - 4" round J-box

Short circuit protection
Overload protection
Thermal protection
Dimmable