

**Description:**

The Ciro II line voltage pendant includes a 4" kiss mono-point canopy. Standard cable length of 59 inches can be easily adjusted in field or specified when ordering. Offered with GU24 or Edison E26 Medium Base.

Part Numbers:

110119bz/MP	bronze, GU24, white fritted glass
110119bz/IN/MP	bronze, medium base, white fritted glass
110119mc/MP	matte chrome, GU24, white fritted glass
110119mc/IN/MP	matte chrome, medium base, white fritted glass
110121bz/MP	bronze, GU24, gold-leaf glass
110121bz/IN/MP	bronze, medium base, gold-leaf glass
110121mc/MP	matte chrome, GU24, gold-leaf glass
110121mc/IN/MP	matte chrome, medium base, gold-leaf glass
110122bz/MP	bronze, GU24, red glass
110122bz/IN/MP	bronze, medium base, red glass
110122mc/MP	matte chrome, GU24, red glass
110122mc/IN/MP	matte chrome, medium base, red glass
110123bz/MP	bronze, GU24, lava glass
110123bz/IN/MP	bronze, medium base, lava glass
110123mc/MP	matte chrome, GU24, lava glass
110123mc/IN/MP	matte chrome, medium base, lava glass

Technical Specs:**Energy Star**

120VAC input

28W Maximum

GU24 socket

Energy Star Compliant

Suitable for dry locations only

Mount to 3" - 4" round J-box

Dimmable (dimmmable lamp required)

Medium E26 Base

120VAC input

100 VA, 100W for 1 (max 100 Watt lamp)

Medium E26 Base

Dimmable