


INSTALLATION AND WIRING DIAGRAM

INDIVIDUAL

HAVANA II LED DOWN

ART. NO. 135 700ch/MP chrome
135 700mc/MP matte chrome



IMPORTANT SAFETY INSTRUCTIONS



1. Save these instructions and refer to them when additions to or changes to the fixture are made.
2. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH THE APPLICABLE NEC CODE.
3. Do not install this fixture in damp or wet locations.
4. CAUTION - Do not install any fixture assembly closer than 6 inches from any curtain, or similar combustible material.
5. Turn off power prior to any work on the systems.
6. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE FIXTURE

Contents of Delivery:

HAVANA II LED DOWN - qty. (1)

Step 1.

- Connect the two wires from the driver (A) to the power cables in the wall.
- Ground the wire in accordance with local electrical code.

Step 2.

- Align the screws (B) with the J-box and tighten until firmly connected. Adjust the cable length by loosening the center cable lock (C) and coiling excess cable around the canopy.

Step 3.

- Place the canopy cover (E) over the mounting plate (D) and secure it with the allen screws (F) located on the sides of the base.

