



Job Name:

Contact:

Fixture Type:

Part Number:

LEDRA® R




Description:

The Ledra R is a recessed fixture with a 70° tilt and 360° rotation on fixture head. Pressure fit mounting hardware allows for no screws to be visible. The small size, long life, lack of UV, rich color options, and cool beam allows for a wide variety of applications. 18 awg wire required to connect Ledra to driver, not included. For compatible drivers refer to our [driver section](#).

Part Numbers:

135731bz/s	bronze, white, 10° lens
135731bz/m	bronze, white, 30° lens
135731bz/fl	bronze, white, 45° lens
135731mc/s	matte chrome, white, 10° lens
135731mc/m	matte chrome, white, 30° lens
135731mc/fl	matte chrome, white, 45° lens
135731wh/s	white, white, 10° lens
135731wh/m	white, white, 30° lens
135731wh/fl	white, white, 45° lens
135731-1bz/s	bronze, warm white, 10° lens
135731-1bz/m	bronze, warm white, 30° lens
135731-1bz/fl	bronze, warm white, 45° lens
135731-1mc/s	matte chrome, warm white, 10° lens
135731-1mc/m	matte chrome, warm white, 30° lens
135731-1mc/fl	matte chrome, warm white, 45° lens
135731-1wh/s	white, warm white, 10° lens
135731-1wh/m	white, warm white, 30° lens
135731-1wh/fl	white, warm white, 45° lens



Technical Specs:

700mA DC constant current input
~2.5W for 1 (3 Watt LED)
White source of 140 lumens
Warm White source of 120 lumens
Class II rated
Suitable for dry locations only
1 7/8" hole cutout
Dimmable (with dimming driver)

Warranty:

All 3 Watt LED fixtures are warranted to be free from defects in material and workmanship for three (3) years from date of

delivery.

For full warranty details, please see our terms and conditions

[here](#)