EL27HE26ICA EL27H26ICDA

6" Compact Fluorescent Vertical Mounted Lamp with Integral Electronic Ballast IC Airtight

Adjusts 1 3/8" to Accomodate Ceiling Thickness


P	RN	JECT	INFO	RM	ΔΤΙ	NN.
	110	JLUI				vii.

Project Name:


Fixture Type:

Date:

DIMENSIONS







PRODUCT SPECIFICATIONS

Housing Features: Single wall construction. Thermally protected electronic ballast.

Adjustable socket bracket allows the use of different lamp types and sizes as well as proper and consistent lamp positioning.

EL27HE26ICA & **EL27H26ICDA** for use in insulated ceilings.

EL27HE26ICA & **EL27H26ICDA** meet restricted air flow requirements per ASTM E283 standards.

Lamp: Designed for (1) 26W Quad/Triple compact fluorescent lamp.

Reflector: Clear or Gold aluminum reflector.

EL27HE26ICA = (1) 26W 4 Pin Quad/Triple 120V Electronic Ballast

EL27H26ICDA = (1) 26W 4 Pin Quad/Triple 120/277V Dimming Ballast

Contact ELCO Lighting for details on various types of dimming ballasts available.

IECC and California Title 24 Compliant with frame gasket (included).

INSTALLATION

Junction Box: Pre-wired junction box provided with 1/2" and 3/4" knockout. U.L. listed/C.U.L. listed: for through branch wiring, maximum (8) No. 12 AWG branch circuit conductors (4 in, 4 out). Junction box provided with removable access plates. 4 Romex Cable knockouts with integral strain relief clips for easy installation.

Mounting: Hanger bars span 24" joists can be repositioned 90 degrees.

Mounting Frame: Stamped galvanized steel material for rust and corrosion resistance.

Labels: • U.L. listed for damp locations.

- U.L. listed for feed through.
- U.L. listed for direct contact with insulation.

CATALOG NUMBER

Example:EL27HE26ICA - ELA99SC See trims page for variety of trims available

