
assembly instructions

Family: Avon | Item No. 5553 BN/CM




Drawing 1 - Strap Detail



start here

- 1. Find a clear area in which you can work.
 - 2. Unpack fixture and glass from carton.
 - 3. Carefully review instructions prior to assembly.

Drawing 2 - Fixture Mounting




*** The construction of this fixture will be accomplished by first mounting the mounting strap to the junction box, making all necessary electrical connections, mounting the fixture to the wall and then installing the fixture glass.

- 1. Prepare mounting strap (A) by threading the two long mounting screws (B) into the back of the gull wing bracket - see Drawing 1.
- Be sure the holes into which the screws are threaded match the spacing of holes (D) in the back plate (E) - see Drawings 1 and 2.
- 2. Attach mounting strap (A) to junction box (J) using two 1" screws (C) see Drawing 2.

SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18) AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED **ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.**

Drawing 3 - Fixture Assembly



Make electrical connections from supply wire to fixture lead wires. Refer to instruction sheet (I.S. 18) and follow all instructions to make all necessary wiring connections. Then refer back to this sheet to complete installation of this fixture.

1. To mount fixture, slide backplate (E) over screws (B) and secure with ball knobs (F) see Drawing 2.

- 1. To install glass, remove the spacer (3) and socket ring (4) from the socket (1) see Drawing 2.
- 2. Place glass (2) over the socket (1).
- 3. Slip spacer (3) and thread socket ring (4) back on to socket (1) and hand tighten. Note: Over tightening could cause damage to glass.
- 4. Repeat steps 1-3 for remaining glass.
- 5. Fixture can now be lamped accordingly.

Note: Maximum wattage for 5553 fixture is 75 watts per bulb.

10.9.08