


12V LED/INCANDESCENT DECK & PATIO

UP/DOWN  
ACCENT  
LIGHT



BBR



15659  
Optional Lens  
Accessory

15079 AZT

BARBECUE  
LIGHT



BK

15123 BK

Ordering Guide & Finish	15079 AZT	15123 BK
Housing	Aluminum	Components of durable high heat thermoplastic resin. Lamp shielded by a high heat-resistant flat glass lens sealed for watertight outdoor use. Flexible stem is durable chrome plated steel with heat shrink rubber sleeving. On/off switch is protected by waterproof rubber boot.
Lamp Base	12V T5 wedge base socket	12V bi-pin, high temperature porcelain socket
Supplied Lamp	11.6-W(VA) 912X (17023) (2) Xenon light source Power usage at 12V AC input VA MAX: 11.6-W(VA)	35-W(VA) MR11 Halogen light source Power usage at 12V AC input VA MAX: 35-W(VA)
Incandescent Lamp Options	6.5-W(VA) 918X (17022) 4-W (VA) 901X (17021)	N/A
LED Lamp Options	2W (18039-18041) see page 137. Compares up to 16W Xenon.	N/A
Wiring	70" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	25" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	Stainless Steel surface mounting plate	(1) set wood screws and (1) set machine screws and nuts
Optional Lens Access.	15659 – Lens	N/A
Notes	N/A	For rail or outdoor countertop mount only
Photometric with Supplied Lamp	Distance from Light	Distance from Light
	Foot Candles	Foot Candles