

## 12V LED/INCANDESCENT ACCENT

### ARCHITECTURAL – GRADE ADJUSTABLE



AZT

Illustrated with 15657  
18" mounting stem  
(sold separately)

**15397 AZT**

### MICRO ACCENT – MR 11



AZT

**15398 AZT**

	<b>15397 AZT</b>	<b>15398 AZT</b>
Ordering Guide & Finish	15397 AZT	15398 AZT
Housing	Machined aluminum. Heat-resistant glass is fully sealed and angled for easy water run-off. Cowl is fully adjustable.	Cast Aluminum. Heat-resistant glass is fully sealed.
Lamp Base	12V Incandescent bi-pin, high temperature porcelain socket	12V Incandescent bi-pin, high temperature porcelain socket
Supplied Lamp	Lamp not supplied unless noted	Lamp not supplied unless noted
Incandescent Lamp Options	Power usage at 12V AC input VA MAX: 50-W(VA) MR-16 35-W(VA) Max. Canada 35-W(VA) MR-11 see page 140	Power usage at 12V AC input VA MAX: 35-W(VA) MR-11 20-W(VA) Max. Canada see page 140
LED Lamp Options	4W (18126-18133) see page 137 Compares to 20W Halogen 5W (18134-18141) see page 137 Compares to 35W Halogen	N/A
Wiring	51" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	36" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	8" slotted in-ground stake	8" slotted in-ground stake
Optional Mounting Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15649 – Stem Coupler 15645, 15656, 15657, 15658 or 15570 – Stems	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15649 – Stem Coupler 15645, 15656, 15657, 15658 or 15570 – Stems
Optional Lens Accessories	15683 BK – Louver 15693 BL – Blue Filter	15631 BL – Blue Filter 15632 LIN – Linear Lens 15633 FRO – Frosted Lens 15634 BK – Louver
Notes	Use with the 6" (15645), 12" (15656), 18" (15657) or 24" (15658) mounting stem for dramatic effects.	Our smallest incandescent (1 <sup>7</sup> / <sub>8</sub> " ) accent light