

# INSTALLATION INSTRUCTIONS

Item#P907 (New. 06/16/2012)

## READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

### MOUNTING THE FIXTURE (Fig.1)

1. Shut off the power at the circuit breaker and remove old fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear surface. Take care not to lose any small parts necessary for installation.
3. Attach the Circular Strap (A) to the junction box in the ceiling with two Screws (C). The side of the Circular Strap marked "GND" must face out.

### CONNECTING THE WIRES (Fig. 2)



4. At this point, connect the electrical wire as shown in figure 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixtures Ground Wire to it. Otherwise, connect the fixture Ground Wire directly to the Circular Strap using the Green Screw provided.

### FINISHING THE INSTALLATION (Fig.1)

5. After wires are connected, tuck them carefully into the ceiling junction box, then place the Canopy of the Fixture body (D) over the Circular Strap (A) and secure it against ceiling with Screws (B).
6. Place the Glass shade (I) inside of the Fixture body (D), insert (H) through the hole on the center of Glass shade (I) to the Hex Nut on the bottom of Fixture Body (D).
7. Place the Plastic Washer (G) and Metal Washer (E) over the Nipple (H) and secure with Cap Nut (F).
8. Install 2\*100W A19 bulbs (Not included) in accordance with fixture specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**

Your installation is now complete. Return power and test the fixture.

**Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not**



**IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.**

