

Catalog Number								
Notes	Туре							

Outdoor General Purpose

FEATURES & SPECIFICATIONS

INTENDED USE

Provides focused illumination for outdoor use in residential and light commercial applications. Ideal for walkways, yards, patios, play areas and driveways creating an inviting exterior space as well as providing safety and security.

Rugged, weather and rust resistant die-cast aluminum housing and lens door frame. Fixture is available in bronze or white finish with a tempered pebble glass lens. Hinged door frame and snap on/off latches provide for easy tool-free re-lamping. Fixture can be eave or wall-mounted.

Standard with electronic ballast (120 volt, 60Hz). Starts instantly down to -13°F


Includes (1) 65W GX10q-4 base 6500K triple tube compact fluorecent lamp. Mounting hardware, silicone caulking and threaded cover plate required purchase separately.

CUL listed to US and Canadian safety standards and suitable for wet locations.

Guaranteed for one year against mechanical defects in manufacture. (Excludes lamp)

Floodlight





(A)

DIMENSIONS


Fixture Heads	Lamp Configuration	Model Number	Number of Lamps	(A) Width inches (cm)	(B) Height inches (cm)	(C) Depth inches (cm)	(D) Extension* inches (cm)
Single		0FL2 65F 120 LP	(1) 65W T4 4-pin 6500K triple tube compact fluorescent	13" (33.0)	9" (22.8)	4-1/2" (11.4)	6" (15.2)

- (C) — (B)


All dimensions are in inches (centimeters)

ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as and replacement parts separate catalog numbers.



OFL2 65F (1) 65W T4 4-pin 6500K triple tube compact fluorescent lamp Included



120 volt residential electronic ballast (standard)



Lamp included



Example: OFL2 65F 120 LP BZ

Accessories/Replacement parts

CF65TB65 65W T4 4-pin GX10q-4 base 6500K triple tube compact fluorescent lamp

^{*} Maxium extension from wall

Floodlight Outdoor General Purpose

PHOTOMETRICS

Full photometric data report available within 2 weeks from request. Consult factory.



ODFL.pmd