

| |
|----------------|
| Catalog Number |
| Notes |
| Type |

FEATURES & SPECIFICATIONS

INTENDED USE

Provides task or accent lighting in commercial, retail, hospitality and residential applications. Ideal for use under and over cabinets, display cases, task lighting, office lighting, coves and utility/work areas.

ATTRIBUTES

Durable aluminum construction in a low-profile design. Can be plugged in or direct-wired (splice box and 24" connector cord required for direct-wiring).

Link up to 10' of modular system to one transformer (required, sold separately). Fixtures can be linked end-to-end with the end row connector (sold separately). All fixtures include a 18" linking cord. 3", 24" and 121" connector cords may also be purchased separately.

LEDs have a 50,000 hour L70 rated life. Provides warm color temperature, 3,000K with CRI 85, and even illumination.

Dimmable when used with the optional step dimmer.

All mounting hardware included. Mounting clips allow for quick & easy installation flush or at 30°. All configurations tested to IES LM79 standards.

LISTING

CUL listed to US and Canadian safety standards.

WARRANTY

Guaranteed for three years against mechanical defects in manufacture.

Note: Specifications are subject to change without notice.

Indoor General Purpose


Rayzer™ Modular LED Lighting System



RAYZER™
LED MODULAR LIGHTING SYSTEM

Specifications

| | |
|----------------|---------------|
| Length: RAZ9 - | 9-1/4 (23.5) |
| RAZ12 - | 12-1/4 (31.1) |
| RAZ18 - | 18-1/4 (46.4) |
| RAZ24 - | 24-1/4 (61.6) |



| |
|---------------------|
| Width: 1-1/4 (3.18) |
| Height: 1/2" (1.27) |

All dimensions are in inches (centimeters)

ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: RAZ18

| Series ^{1,2} | Options |
|----------------------------------|-------------------|
| RAZ9 9" length - 3 LEDs | (Consult factory) |
| RAZ12 12" length - 4 LEDs | |
| RAZ18 18" length - 6 LEDs | |
| RAZ24 24" length - 8 LEDs | |

| Accessories / Replacement Parts ^{1,2} | | | |
|--|---|--------------|---|
| RAZTRANS24 120 | 24v transformer - 120v power source | RAZ ERC | End row connector |
| RAZTRANS24 MVOLT | 24v transformer - Multi-Volt power source | RAZ PHD | Power hub distributor |
| RAZDIM | Step dimmer with remote touch pad | RAZ INLS26 | In-line power switch |
| RAZ CC121 | 121" linking cord (fixture to fixture) | UCD JB | Splice box - white (required for direct wire) |
| RAZ CC24 | 24" linking cord (fixture to fixture) | UCD JB BL | Splice box - black (required for direct wire) |
| RAZ CC3 | 3" linking cord (fixture to fixture) | UC ERC24 R12 | 24" connector cord - white (required for direct wire) |
| RAZLVCC | Low voltage linking cord (cord to cord) | UC ERC24 BL | 24" connector cord - black (required for direct wire) |

Notes:

- Link up to 10' of modular system to one transformer.
- Transformer is required for operation.

Rayzer™ LED Modular Lighting System

Full photometric data report available within 2 weeks from request. Consult factory.

| 9" | 12" | 18" | 24" |
|--|--|---|--|
| <p>Acuity Brands Lighting</p> <p>lighting facts^{CM} A Program of the U.S. DOE</p> <p>Light Output (Lumens) 175 Watts 5.4 Lumens per Watt (Efficacy) 32</p> <p>Color Accuracy 85 Color Rendering Index (CRI)</p> <p>Light Color 3000 (Bright White) Correlated Color Temperature (CCT)</p> <p>Warm White 3000K Bright White 4500K Daylight 6500K</p> <p>All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.</p> <p>Visit www.lightingfacts.com for the Label Reference Guide.</p> <p>Registration Number: NISM-1F11Y2 Model Number: RAZ9 (with RAZTRANS24 120 power supply) Type: Under-cabinet kitchen lights</p> | <p>Acuity Brands Lighting</p> <p>lighting facts^{CM} A Program of the U.S. DOE</p> <p>Light Output (Lumens) 239 Watts 7.12 Lumens per Watt (Efficacy) 33</p> <p>Color Accuracy 85 Color Rendering Index (CRI)</p> <p>Light Color 3000 (Bright White) Correlated Color Temperature (CCT)</p> <p>Warm White 3000K Bright White 4500K Daylight 6500K</p> <p>All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.</p> <p>Visit www.lightingfacts.com for the Label Reference Guide.</p> <p>Registration Number: NISM-1S7U7X Model Number: RAZ12 (with RAZTRANS24 120 power supply) Type: Under-cabinet kitchen lights</p> | <p>Acuity Brands Lighting</p> <p>lighting facts^{CM} A Program of the U.S. DOE</p> <p>Light Output (Lumens) 353 Watts 9.7 Lumens per Watt (Efficacy) 36</p> <p>Color Accuracy 85 Color Rendering Index (CRI)</p> <p>Light Color 3000 (Bright White) Correlated Color Temperature (CCT)</p> <p>Warm White 3000K Bright White 4500K Daylight 6500K</p> <p>All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.</p> <p>Visit www.lightingfacts.com for the Label Reference Guide.</p> <p>Registration Number: NISM-RY3L37 Model Number: RAZ18 (with RAZTRANS24 120 power supply) Type: Under-cabinet kitchen lights</p> | <p>Lithonia Lighting</p> <p>lighting facts^{CM} A Program of the U.S. DOE</p> <p>Light Output (Lumens) 441 Watts 13.14 Lumens per Watt (Efficacy) 33</p> <p>Color Accuracy 85 Color Rendering Index (CRI)</p> <p>Light Color 3000 (Bright White) Correlated Color Temperature (CCT)</p> <p>Warm White 3000K Bright White 4500K Daylight 6500K</p> <p>All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.</p> <p>Visit www.lightingfacts.com for the Label Reference Guide.</p> <p>Registration Number: NISM-248QH8 Model Number: RAZ24 (w/ RAZTRANS24 120 power supply) Type: Under-cabinet kitchen lights</p> |

INSTALLATION DIAGRAM

Note: Fixture includes 18" linking cord, mounting clips for flush or 30° mounting, and screws.

