

Lighting Your Life Since 1970

Product Specifications - 3138CDSE			
Job Name:	Job Type:		
Quantity:	Comments		



3138CDSE

Santa Barbara Cast 3-Light Outdoor Hanging Lantern

Finish	Glass/Shade	Product Category
Sienna	Seedy	Outdoor Hanging Lantern

Lamping	9
Number	(

Lamping	
Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Measurements

Width	9.0"
Height	17.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	7.9 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	144"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	7.9 lbs
Carton Width	13"
Carton Height	27"
Carton Length	13"
Carton Cubic Feet	2.48
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

N/A N/A

Certification Other **Equivalents**

00.1041.0		0 (1101		=94.14.00
Safety Rating	Wet	UPC Code	783209313804	Incandescent Watts
Energy Star	No	Shades Included	N/A	Fluorescent Watts
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Die Cast Aluminum	

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.