
# Incandescent



#### Outdoor

Type -30



				P5	704			
				P5	705			
		Finish		P5	P5706  Dimensions (Inches)			
Cata	alog Whi	te	-	ļ				
No.			Lamping	Α	В	С		
P57	704 -30		1 (m) 60w	10-1/2	5-7/8	3-3/4		
P57	705 -30		1 (m) 60w	10-1/2	5-7/8	4		
P57	706 -30		1 (m) 60w	10-1/2	5-7/8	4		
A			5705 with grill		P570	06 with hood	B J	

## **Specifications:**

<u>General</u>

- UV stabilized ribbed frosted polycarbonate oval lens: 10-1/4", 5-5/8" ht., 2-13/16" depth
- White (-30) finish
- Polycarbonate back plate and frame (grill or hood)
- Lamp replacement remove screws holding the frame
- Units can be used for shower light applications
- Complies with "Americans with Disabilities Act" ADA

## <u>Mounting</u>

- Wall mount
- Back plate covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included

#### **Electrical**

- Medium base ceramic socket
- Pre-wired

#### <u>Labeling</u>

UL-CUL Wet location listed

Progress Lighting 701 Millennium Blvd. Greenville, South Carolina 29607