

INSTALLATION INSTRUCTIONS

For Model 8726-A615B

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

CONNECTING THE WIRES (Fig. 2)

1. Shut off power at the circuit breaker and remove the old fixture.
2. Pull black, white and ground wires out of the post.
3. Next, connect the electrical wires as shown in Fig. 2, while supporting the fixture. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. If not, consult your electrician for proper grounding.

MOUNTING THE FIXTURE (Fig.1)

4. After wires are connected, tuck them carefully inside the post cup (D). Align the lantern with the post and secure with sheet metal screws (E).
5. Install the bulb(s) in accordance with the fixture's specification. **(DO NOT EXCEED MAXIMUM WATTAGE RATING) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**

ASSEMBLING THE FIXTURE (Fig. 1)

6. For installing the bulbs or replacing the bulbs at a later date, remove knurled knobs (C), remove roof (A). After the installation, replace roof (A) and secure with knurled knobs (C).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

