INSTALLATION INSTRUCTIONS

Item#72020-A179-PL(Rev. 06/11/2011)
READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

MOUNTING THE BACKPLATE (Fig.1)

- Shut off the power at the circuit breaker and remove the old fixture, including the mounting hardware.
- Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3. Attach the back plate (A) to the Junction box with Screws (B). The side of the back plate marked "GND" must face out.

CONNECTING THE WIRES (Fig. 2)

4. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the back plate using the green screw provided. After the wires are connected carefully tuck them inside the junction box.

COMPLETING THE INSTALLATION

- 5. Place the fixture body (D) over the back plate (A), and secure with screws (C).
- To prevent moisture from entering the outlet box and causing a short, use clear caulking (i.e. Indoor/Outdoor Silicone Sealant) to outline the outside of fixture back-plate where it meets the wall leaving a space at bottom to allow moisture a means to escape (Fig.3).
- 7. Install the CFL 1*26W bulb (F) (included) into socket (E) in accordance with the fixture's specification. (DO NOT EXCEED THE SPECIFIED WATTAGE!)
- 8. The ballast and lamp are combined, to replace or install, twist pins into socket as shown on Fig 4.
- 9. Install the glass panel (G) into fixture body (D) and secure with the cap nut and clips provided
- 10. This fixture contains an integrated photo sensor that automatically prevents operating during daylight hours.
- 11. This fixture is rated for a minimum start temperature of 0 degrees Fahrenheit (-17 degree Celsius).
- 12. This fixture is UL Listed for Wet Location applications..

Your installation is now complete. Return power and test the fixture. Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

The color correlated Temperature (CCT) for replacing the enclosed lamp is (2700K).

<u>Caution</u>: CFLs contain Mercury (Hg) Dispose of according to Local, State and Federal Law. (www.epa.gov/bulbrecycling).

LIMITED 2 YEAR WARRANTY

This Fixture is covered by a Limited 2 year Warranty from the Manufacturer, effective from the date of purchase. This fixture is warranted against defects in the quality of the housing, trims, diffuser, shades, and electrical components. Fixture finishes and/or lamps (bulbs) are expressly excluded from this warranty; refer to bulb manufacturer for lamp warranty. This Fixture, if supplied with an automatic shut off sensor, motion control sensor, or photocell, cannot be installed in conjunction with any other device without voiding warranty. Modifying this fixture or use of another non-provided control will also void Product Warranty and UL listing.









